

Eiche Grauwald

- ◇ Natural wood look
- ◇ Dimensionally stable and water resistant
- ◇ Large areas can be laid (up to 400 m²)
- ◇ Only 4,5 mm mounting height
- ◇ Format 1220 x 181 mm
- ◇ Wear layer 0,3 mm
- ◇ Carton content 12 planks = 2,650 m²
- ◇ Suitable for hot water and electric underfloor heating
- ◇ Patented 2G click connection
- ◇ Low emissions (Certified A+)
- ◇ Integrated underlay mat
- ◇ Impact sound reduction up to 18 dB
- ◇ Utilization class 23/32

To note before laying:


- Quantity required +10% of the area
- Subfloor clean, hard, level, stable and firm
- Level out unevenness (max. 3 mm per 1,2 m)
- We recommend that the floorboards lie horizontally in the room for at least 24 hours to acclimate!
- **Important:** room temperature = floor temperature during installation
- Use temperature 15°C to 60°C

Please note when laying:

- On linoleum, wood/pulp panels: 0,2 mm PE construction foil is absolutely necessary for decoupling!
- The planks must be clicked in correctly
- Provide expansion joints to walls and fixed objects of > 8 mm
- Maximum free-standing field size 20 x 20 m (400 m²) Layable without expansion joints
- **Do not use** an additional underlay mat!

The pictures may differ in color from the original product.

Article-No.	Decor-No.	Description	EAN	Pack/Pallet
106203820	ST3763-03	Swiss Edition SPC, Eiche Grauwald	7640165929834	36



Eiche Gent

- ◇ Natural wood look
- ◇ Dimensionally stable and water resistant
- ◇ Large areas can be laid (up to 400 m²)
- ◇ Only 4,5 mm mounting height
- ◇ Format 1220 x 181 mm
- ◇ Wear layer 0,3 mm
- ◇ Carton content 12 planks = 2,650 m²
- ◇ Suitable for hot water and electric underfloor heating
- ◇ Patented 2G click connection
- ◇ Low emissions (Certified A+)
- ◇ Integrated underlay mat
- ◇ Impact sound reduction up to 18 dB
- ◇ Utilization class 23/32

To note before laying:

- Quantity required +10% of the area
- Subfloor clean, hard, level, stable and firm
- Level out unevenness (max. 3 mm per 1,2 m)
- We recommend that the floorboards lie horizontally in the room for at least 24 hours to acclimate!
- **Important:** room temperature = floor temperature during installation
- Use temperature 15°C to 60°C


Please note when laying:

- On linoleum, wood/pulp panels: 0,2 mm PE construction foil is absolutely necessary for decoupling!
- The planks must be clicked in correctly
- Provide expansion joints to walls and fixed objects of > 8 mm
- Maximum free-standing field size 20 x 20 m (400 m²) Layable without expansion joints
- **Do not use** an additional underlay mat!



The pictures may differ in color from the original product.

Article-No.	Decor-No.	Description	EAN	Pack/Pallet
106203821	ST3739-03	Swiss Edition SPC, Eiche Gent	7640165929841	36



Eiche Denver

- ◇ Natural wood look
- ◇ Dimensionally stable and water resistant
- ◇ Large areas can be laid (up to 400 m²)
- ◇ Only 4,5 mm mounting height
- ◇ Format 1220 x 181 mm
- ◇ Wear layer 0,3 mm
- ◇ Carton content 12 planks = 2,650 m²
- ◇ Suitable for hot water and electric underfloor heating
- ◇ Patented 2G click connection
- ◇ Low emissions (Certified A+)
- ◇ Integrated underlay mat
- ◇ Impact sound reduction up to 18 dB
- ◇ Utilization class 23/32

To note before laying:


- Quantity required +10% of the area
- Subfloor clean, hard, level, stable and firm
- Level out unevenness (max. 3 mm per 1,2 m)
- We recommend that the floorboards lie horizontally in the room for at least 24 hours to acclimate!
- **Important:** room temperature = floor temperature during installation
- Use temperature 15°C to 60°C

Please note when laying:

- On linoleum, wood/pulp panels: 0,2 mm PE construction foil is absolutely necessary for decoupling!
- The planks must be clicked in correctly
- Provide expansion joints to walls and fixed objects of > 8 mm
- Maximum free-standing field size 20 x 20 m (400 m²) Layable without expansion joints
- **Do not use** an additional underlay mat!

The pictures may differ in color from the original product.

Article-No.	Decor-No.	Description	EAN	Pack/Pallet
106203822	ST3632-16	Swiss Edition SPC, Eiche Denver	7640165929858	36



Eiche Posen

- ◇ Natural wood look
- ◇ Dimensionally stable and water resistant
- ◇ Large areas can be laid (up to 400 m²)
- ◇ Only 4,5 mm mounting height
- ◇ Format 1220 x 181 mm
- ◇ Wear layer 0,3 mm
- ◇ Carton content 12 planks = 2,650 m²
- ◇ Suitable for hot water and electric underfloor heating
- ◇ Patented 2G click connection
- ◇ Low emissions (Certified A+)
- ◇ Integrated underlay mat
- ◇ Impact sound reduction up to 18 dB
- ◇ Utilization class 23/32

To note before laying:


- Quantity required +10% of the area
- Subfloor clean, hard, level, stable and firm
- Level out unevenness (max. 3 mm per 1,2 m)
- We recommend that the floorboards lie horizontally in the room for at least 24 hours to acclimate!
- **Important:** room temperature = floor temperature during installation
- Use temperature 15°C to 60°C

Please note when laying:

- On linoleum, wood/pulp panels: 0,2 mm PE construction foil is absolutely necessary for decoupling!
- The planks must be clicked in correctly
- Provide expansion joints to walls and fixed objects of > 8 mm
- Maximum free-standing field size 20 x 20 m (400 m²) Layable without expansion joints
- **Do not use** an additional underlay mat!

The pictures may differ in color from the original product.

Article-No.	Decor-No.	Description	EAN	Pack/Pallet
106203823	ST2082L-04	Swiss Edition SPC, Eiche Posen	7640165929865	36



Eiche Bruchstein


- ◇ Natural wood look
- ◇ Dimensionally stable and water resistant
- ◇ Large areas can be laid (up to 400 m²)
- ◇ Only 4,5 mm mounting height
- ◇ Format 1220 x 181 mm
- ◇ Wear layer 0,3 mm
- ◇ Carton content 12 planks = 2,650 m²
- ◇ Suitable for hot water and electric underfloor heating
- ◇ Patented 2G click connection
- ◇ Low emissions (Certified A+)
- ◇ Integrated underlay mat
- ◇ Impact sound reduction up to 18 dB
- ◇ Utilization class 23/32

To note before laying:

- Quantity required +10% of the area
- Subfloor clean, hard, level, stable and firm
- Level out unevenness (max. 3 mm per 1,2 m)
- We recommend that the floorboards lie horizontally in the room for at least 24 hours to acclimate!
- **Important:** room temperature = floor temperature during installation
- Use temperature 15°C to 60°C

Please note when laying:

- On linoleum, wood/pulp panels: 0,2 mm PE construction foil is absolutely necessary for decoupling!
- The planks must be clicked in correctly
- Provide expansion joints to walls and fixed objects of > 8 mm
- Maximum free-standing field size 20 x 20 m (400 m²) Layable without expansion joints
- **Do not use** an additional underlay mat!



The pictures may differ in color from the original product.

Article-No.	Decor-No.	Description	EAN	Pack/Pallet
106203824	ST190L-22	Swiss Edition SPC, Eiche Bruchstein	7640165929872	36



Eiche Ottawa

- ◇ Natural wood look
- ◇ Dimensionally stable and water resistant
- ◇ Large areas can be laid (up to 400 m²)
- ◇ Only 4,5 mm mounting height
- ◇ Format 1220 x 181 mm
- ◇ Wear layer 0,3 mm
- ◇ Carton content 12 planks = 2,650 m²
- ◇ Suitable for hot water and electric underfloor heating
- ◇ Patented 2G click connection
- ◇ Low emissions (Certified A+)
- ◇ Integrated underlay mat
- ◇ Impact sound reduction up to 18 dB
- ◇ Utilization class 23/32

To note before laying:

- Quantity required +10% of the area
- Subfloor clean, hard, level, stable and firm
- Level out unevenness (max. 3 mm per 1,2 m)
- We recommend that the floorboards lie horizontally in the room for at least 24 hours to acclimate!
- **Important:** room temperature = floor temperature during installation
- Use temperature 15°C to 60°C

Please note when laying:

- On linoleum, wood/pulp panels: 0,2 mm PE construction foil is absolutely necessary for decoupling!
- The planks must be clicked in correctly
- Provide expansion joints to walls and fixed objects of > 8 mm
- Maximum free-standing field size 20 x 20 m (400 m²) Layable without expansion joints
- **Do not use** an additional underlay mat!

The pictures may differ in color from the original product.

Article-No.	Decor-No.	Description	EAN	Pack/Pallet
106203825	ST0354-17	Swiss Edition SPC, Eiche Ottawa	7640165929889	36