



Mississippi Oak

- ◇ Synchronized pore optics (EIR)
- ◇ Dimensionally stable & water resistant
- ◇ Endless decor variation
- ◇ Large areas can be laid (up to 400 m²)
- ◇ Only 4,8 mm mounting height
- ◇ Format 1220 x 228 mm
- ◇ Wear layer 0,5 mm
- ◇ Carton content 10 planks = 2,782 m²
- ◇ Suitable for hot water and electric underfloor heating
- ◇ Drop Down I4F click connection
- ◇ Low emissions (Certified A+)
- ◇ Integrated underlay mat
- ◇ Impact sound reduction up to 18 dB
- ◇ Utilization class 23/33

To note before laying:

- Quantity required +10% of the area
- Subfloor clean, hard, level, stable and firm
- Level out unevenness (max. 3 mm per 1,2 m)
- We recommend that the floorboards lie horizontally in the room for at least 24 hours to acclimate!
- **Important:** room temperature = floor temperature during installation
- Use temperature 15°C to 60°C

Please note when laying:

- On linoleum, wood/pulp panels: 0,2 mm PE construction foil is absolutely necessary for decoupling!
- The planks must be clicked in correctly
- Provide expansion joints to walls and fixed objects of > 8 mm
- Maximum free-standing field size 20 x 20 m (400 m²) Layable without expansion joints
- **Do not use** an additional underlay mat!



The pictures may differ in color from the original product.

| Article-No. | Decor-No. | Description | EAN | Pack/Pallet |
|-------------|------------|------------------------------------|---------------|-------------|
| 106203802 | ST190EL-09 | Swiss Edition SPC, Mississippi Oak | 7640165929919 | 33 |



Alabama Oak

- ◇ Synchronized pore optics (EIR)
- ◇ Dimensionally stable & water resistant
- ◇ Endless decor variation
- ◇ Large areas can be laid (up to 400 m²)
- ◇ Only 4,8 mm mounting height
- ◇ Format 1220 x 228 mm
- ◇ Wear layer 0,5 mm
- ◇ Carton content 10 planks = 2,782 m²
- ◇ Suitable for hot water and electric underfloor heating
- ◇ Drop Down I4F click connection
- ◇ Low emissions (Certified A+)
- ◇ Integrated underlay mat
- ◇ Impact sound reduction up to 18 dB
- ◇ Utilization class 23/33

To note before laying:

- Quantity required +10% of the area
- Subfloor clean, hard, level, stable and firm
- Level out unevenness (max. 3 mm per 1,2 m)
- We recommend that the floorboards lie horizontally in the room for at least 24 hours to acclimate!
- **Important:** room temperature = floor temperature during installation
- Use temperature 15°C to 60°C


Please note when laying:

- On linoleum, wood/pulp panels: 0,2 mm PE construction foil is absolutely necessary for decoupling!
- The planks must be clicked in correctly
- Provide expansion joints to walls and fixed objects of > 8 mm
- Maximum free-standing field size 20 x 20 m (400 m²) Layable without expansion joints
- **Do not use** an additional underlay mat!



The pictures may differ in color from the original product.

| Article-No. | Decor-No. | Description | EAN | Pack/Pallet |
|-------------|-------------|--------------------------------|---------------|-------------|
| 106203803 | STW3632W-45 | Swiss Edition SPC, Alabama Oak | 7640165929926 | 33 |



Carolina Oak

- ◇ Synchronized pore optics (EIR)
- ◇ Dimensionally stable & water resistant
- ◇ Endless decor variation
- ◇ Large areas can be laid (up to 400 m²)
- ◇ Only 4,8 mm mounting height
- ◇ Format 1220 x 228 mm
- ◇ Wear layer 0,5 mm
- ◇ Carton content 10 planks = 2,782 m²
- ◇ Suitable for hot water and electric underfloor heating
- ◇ Drop Down I4F click connection
- ◇ Low emissions (Certified A+)
- ◇ Integrated underlay mat
- ◇ Impact sound reduction up to 18 dB
- ◇ Utilization class 23/33

To note before laying:

- Quantity required +10% of the area
- Subfloor clean, hard, level, stable and firm
- Level out unevenness (max. 3 mm per 1,2 m)
- We recommend that the floorboards lie horizontally in the room for at least 24 hours to acclimate!
- **Important:** room temperature = floor temperature during installation
- Use temperature 15°C to 60°C


Please note when laying:

- On linoleum, wood/pulp panels: 0,2 mm PE construction foil is absolutely necessary for decoupling!
- The planks must be clicked in correctly
- Provide expansion joints to walls and fixed objects of > 8 mm
- Maximum free-standing field size 20 x 20 m (400 m²) Layable without expansion joints
- **Do not use** an additional underlay mat!



The pictures may differ in color from the original product.

| Article-No. | Decor-No. | Description | EAN | Pack/Pallet |
|-------------|-------------|---------------------------------|---------------|-------------|
| 106203800 | STW3632W-22 | Swiss Edition SPC, Carolina Oak | 7640165929896 | 33 |



Key West Oak

- ◇ Synchronized pore optics (EIR)
- ◇ Dimensionally stable & water resistant
- ◇ Endless decor variation
- ◇ Large areas can be laid (up to 400 m²)
- ◇ Only 4,8 mm mounting height
- ◇ Format 1220 x 228 mm
- ◇ Wear layer 0,5 mm
- ◇ Carton content 10 planks = 2,782 m²
- ◇ Suitable for hot water and electric underfloor heating
- ◇ Drop Down I4F click connection
- ◇ Low emissions (Certified A+)
- ◇ Integrated underlay mat
- ◇ Impact sound reduction up to 18 dB
- ◇ Utilization class 23/33

To note before laying:


- Quantity required +10% of the area
- Subfloor clean, hard, level, stable and firm
- Level out unevenness (max. 3 mm per 1,2 m)
- We recommend that the floorboards lie horizontally in the room for at least 24 hours to acclimate!
- **Important:** room temperature = floor temperature during installation
- Use temperature 15°C to 60°C

Please note when laying:

- On linoleum, wood/pulp panels: 0,2 mm PE construction foil is absolutely necessary for decoupling!
- The planks must be clicked in correctly
- Provide expansion joints to walls and fixed objects of > 8 mm
- Maximum free-standing field size 20 x 20 m (400 m²) Layable without expansion joints
- **Do not use** an additional underlay mat!

The pictures may differ in color from the original product.

| Article-No. | Decor-No. | Description | EAN | Pack/Pallet |
|-------------|------------|---------------------------------|---------------|-------------|
| 106203804 | ST190EL-02 | Swiss Edition SPC, Key West Oak | 7640165929933 | 33 |



Oklahoma Oak

- ◇ Synchronized pore optics (EIR)
- ◇ Dimensionally stable & water resistant
- ◇ Endless decor variation
- ◇ Large areas can be laid (up to 400 m²)
- ◇ Only 4,8 mm mounting height
- ◇ Format 1220 x 228 mm
- ◇ Wear layer 0,5 mm
- ◇ Carton content 10 planks = 2,782 m²
- ◇ Suitable for hot water and electric underfloor heating
- ◇ Drop Down I4F click connection
- ◇ Low emissions (Certified A+)
- ◇ Integrated underlay mat
- ◇ Impact sound reduction up to 18 dB
- ◇ Utilization class 23/33

To note before laying:

- Quantity required +10% of the area
- Subfloor clean, hard, level, stable and firm
- Level out unevenness (max. 3 mm per 1,2 m)
- We recommend that the floorboards lie horizontally in the room for at least 24 hours to acclimate!
- **Important:** room temperature = floor temperature during installation
- Use temperature 15°C to 60°C

Please note when laying:

- On linoleum, wood/pulp panels: 0,2 mm PE construction foil is absolutely necessary for decoupling!
- The planks must be clicked in correctly
- Provide expansion joints to walls and fixed objects of > 8 mm
- Maximum free-standing field size 20 x 20 m (400 m²) Layable without expansion joints
- **Do not use** an additional underlay mat!



The pictures may differ in color from the original product.

| Article-No. | Decor-No. | Description | EAN | Pack/Pallet |
|-------------|------------|---------------------------------|---------------|-------------|
| 106203801 | ST190EL-07 | Swiss Edition SPC, Oklahoma Oak | 7640165929902 | 33 |