

# BARIDECOR AQUA



## MANUFACTURER

BARNIZADOS INDUSTRIALES S.A.  
Camino Frailes S/N, Santa Bárbara,  
43570 Tarragona (SPAIN)  
Phone +34 977 718 000 Fax +34 977 718 261  
bariperfil@bariperfil.es | bariperfil.es

## PRODUCT

BARIDECOR AQUA vinyl panel, 4mm thick, in 600mm x 300mm tile format and has a density of 650 kg/m<sup>3</sup>. It is a specific coating for walls. The variety of designs of the BARIDECOR AQUA, is carry out through a process of 3D scanning of natural materials (stones, concrete, wood, etc.). The print of the panels is through digital printing technology. Both technologies allow us to give infinite solutions in interior design and in the habitat sector.

Information provided by the manufacturer under its own responsibility.

## TESTS CARRIED OUT

Resistance to scratching (N)  
Resistance to cold liquids (1hour)  
Lightfastness (grey scale grade)  
Indentation test

Determinations of openings and height difference between elements:

- Openings between elements (mm)
  - Medium value / maximum value
- Height different (mm)
  - Medium value / maximum value

Dimensional stability:

- Increase in length
  - Parallel (mm/m)
  - Cross (mm/m)
- Increased thickness
  - Parallel (%)
  - Cross (%)
- Increase in mass (%)

Aging at conditioning chamber at 35°C and 85% RH (two weeks) and subsequently application of a static charge of 5 kg.

Reaction to fire (Classification)

Recyclability

## STANDARDS

UNE EN 15186:2012  
UNE EN 12720:09+A1:2014  
UNE EN 15187:07  
UNE EN 13329:07+A1:2009

UNE EN 13329:07+A1:2009

UNE EN 318:2002

According to internal method

UNE-EN 13501-1:07 + A1:2010

Recycling process according internal method  
Checking according to  
EN ISO 178:11/A1:13  
EN ISO 179-1:11

## RESULT

13  
5 (two designs)  
4/5 (two designs)  
Residual indentation 0,20mm

0,2 / 0,5

0,17 / 0,37

Low to high HR	High to low HR
0,17	-0.03
1,39	-0.03

0,5	-0.5
0,3	-0,3
0,1	-0,1

No adhesion failures

E

Recyclable product  
(AT-1684/15 de 7-01-2016).