



The pictures may differ in color from the original product.

## White Oak

- ◇ Natural wood look
- ◇ Quiet and warm underfoot
- ◇ Only 4,2 mm mounting height
- ◇ Wear layer 0,3 mm
- ◇ **L 1220 x B 180 mm**
- ◇ Carton content = 10 planks = 2,196 m<sup>2</sup>
- ◇ 100% recyclable
- ◇ Simple, floating floor laying
- ◇ Patented Uniclic connection
- ◇ Low emissions (Certified A +)
- ◇ DIBT certified
- ◇ Sound reduction up to 5 dB
- ◇ Utilization class 23/31

### Note before laying:

- Amount needed + 10% of the area
- Clean underlay, hard, flat, stable and strong
- Uneven surface = max 3 mm per 1,2 m
- Acclimatize the planks horizontally in the room for at least 48h!
- Important: room temperature = soil temperature = use temperature 18 ° C to 24 ° C

### Points to note about the configuration:

- If underlay required: flameproof, vinyl approved (at least 400 kPa/m<sup>2</sup>, 1.5 mm, non-adhesive)
- On linoleum, wood-based flooring: 0,2 mm PE Films building for decoupling mandatory!
- The planks must be properly clicked in!
- Provide expansion joints to walls and fixed objects of 8-10 mm
- Maximum field size 10 x 10 m

Decor	Article No.	Description	EAN	Pack/Pallet
MB1117-10	106202175	Basico, Weiss Eiche, 4,2 mm	7640165922132	48



The pictures may differ in color from the original product.

### Core Oak

- ◇ Natural wood look
- ◇ Quiet and warm underfoot
- ◇ Only 4,2 mm mounting height
- ◇ Wear layer 0,3 mm
- ◇ **L 1220 x B 180 mm**
- ◇ Carton content = 10 planks = 2,196 m<sup>2</sup>
- ◇ 100% recyclable
- ◇ Simple, floating floor laying
- ◇ Patented Uniclic connection
- ◇ Low emissions (Certified A +)
- ◇ DIBT certified
- ◇ Sound reduction up to 5 dB
- ◇ Utilization class 23/31

#### Note before laying:

- Amount needed + 10% of the area
- Clean underlay, hard, flat, stable and strong
- Uneven surface = max 3 mm per 1,2 m
- Acclimatize the planks horizontally in the room for at least 48h!
- Important: room temperature = soil temperature = use temperature 18 ° C to 24 ° C

#### Points to note about the configuration:

- If underlay required: flameproof, vinyl approved (at least 400 kPa/m<sup>2</sup>, 1.5 mm, non-adhesive)
- On linoleum, wood-based flooring: 0,2 mm PE Films building for decoupling mandatory!
- The planks must be properly clicked in!
- Provide expansion joints to walls and fixed objects of 8-10 mm
- Maximum field size 10 x 10 m

Decor	Article No.	Description	EAN	Pack/Pallet
MB02219-04	106202176	Basico, Kern Eiche, 4,2 mm	7640165923023	48



**UNICLIC**®  
PROFESSOR DR. KIMBERLY D. SMITH, Ph.D. UNICLIC® IS A REGISTERED TRADEMARK

The pictures may differ in color from the original product.

### Pine Scandic

- ◇ Natural wood look
- ◇ Quiet and warm underfoot
- ◇ Only 4,2 mm mounting height
- ◇ Wear layer 0,3 mm
- ◇ **L 1220 x B 180 mm**
- ◇ Carton content = 10 planks = 2,196 m<sup>2</sup>
- ◇ 100% recyclable
- ◇ Simple, floating floor laying
- ◇ Patented Uniclic connection
- ◇ Low emissions (Certified A +)
- ◇ DIBT certified
- ◇ Sound reduction up to 5 dB
- ◇ Utilization class 23/31

**Note before laying:**

- Amount needed + 10% of the area
- Clean underlay, hard, flat, stable and strong
- Uneven surface = max 3 mm per 1,2 m
- Acclimatize the planks horizontally in the room for at least 48h!
- Important: room temperature = soil temperature = use temperature 18 ° C to 24 ° C

**Points to note about the configuration:**

- If underlay required: flameproof, vinyl approved (at least 400 kPa/m<sup>2</sup>, 1.5 mm, non-adhesive)
- On linoleum, wood-based flooring: 0,2 mm PE Films building for decoupling mandatory!
- The planks must be properly clicked in!
- Provide expansion joints to walls and fixed objects of 8-10 mm
- Maximum field size 10 x 10 m



Decor	Article No.	Description	EAN	Pack/Pallet
MH07239	106202177	Basico, Kiefer Scandic, 4,2 mm	7640165923030	48



The pictures may differ in color from the original product.

### Oak Habsburg

- ◇ Natural wood look
- ◇ Quiet and warm underfoot
- ◇ Only 4,2 mm mounting height
- ◇ Wear layer 0,3 mm
- ◇ **L 1220 x B 180 mm**
- ◇ Carton content = 10 planks = 2,196 m<sup>2</sup>
- ◇ 100% recyclable
- ◇ Simple, floating floor laying
- ◇ Patented Uniclic connection
- ◇ Low emissions (Certified A +)
- ◇ DIBT certified
- ◇ Sound reduction up to 5 dB
- ◇ Utilization class 23/31

**Note before laying:**

- Amount needed + 10% of the area
- Clean underlay, hard, flat, stable and strong
- Uneven surface = max 3 mm per 1,2 m
- Acclimatize the planks horizontally in the room for at least 48h!
- Important: room temperature = soil temperature = use temperature 18 ° C to 24 ° C

**Points to note about the configuration:**

- If underlay required: flameproof, vinyl approved (at least 400 kPa/m<sup>2</sup>, 1.5 mm, non-adhesive)
- On linoleum, wood-based flooring: 0,2 mm PE Films building for decoupling mandatory!
- The planks must be properly clicked in!
- Provide expansion joints to walls and fixed objects of 8-10 mm
- Maximum field size 10 x 10 m

Decor	Article No.	Description	EAN	Pack/Pallet
MY058-04	106202178	Basico, Eiche Habsburg, 4,2 mm	7640165923047	48



The pictures may differ in color from the original product.

### Fulda Pine

- ◇ Natural wood look
- ◇ Quiet and warm underfoot
- ◇ Only 4,2 mm mounting height
- ◇ Wear layer 0,3 mm
- ◇ **L 1220 x B 180 mm**
- ◇ Carton content = 10 planks = 2,196 m<sup>2</sup>
- ◇ 100% recyclable
- ◇ Simple, floating floor laying
- ◇ Patented Uniclic connection
- ◇ Low emissions (Certified A +)
- ◇ DIBT certified
- ◇ Sound reduction up to 5 dB
- ◇ Utilization class 23/31

**Note before laying:**

- Amount needed + 10% of the area
- Clean underlay, hard, flat, stable and strong
- Uneven surface = max 3 mm per 1,2 m
- Acclimatize the planks horizontally in the room for at least 48h!
- Important: room temperature = soil temperature = use temperature 18 ° C to 24 ° C

**Points to note about the configuration:**

- If underlay required: flameproof, vinyl approved (at least 400 kPa/m<sup>2</sup>, 1.5 mm, non-adhesive)
- On linoleum, wood-based flooring: 0,2 mm PE Films building for decoupling mandatory!
- The planks must be properly clicked in!
- Provide expansion joints to walls and fixed objects of 8-10 mm
- Maximum field size 10 x 10 m



Decor	Article No.	Description	EAN	Pack/Pallet
MO 0258-2	106202179	Basico, Fulda Kiefer, 4,2 mm	7640165923054	48



The pictures may differ in color from the original product.

### Ashton

- ◇ Natural wood look
- ◇ Quiet and warm underfoot
- ◇ Only 4,2 mm mounting height
- ◇ Wear layer 0,3 mm
- ◇ **L 1220 x B 180 mm**
- ◇ Carton content = 10 planks = 2,196 m<sup>2</sup>
- ◇ 100% recyclable
- ◇ Simple, floating floor laying
- ◇ Patented Uniclic connection
- ◇ Low emissions (Certified A +)
- ◇ DIBT certified
- ◇ Sound reduction up to 5 dB
- ◇ Utilization class 23/31

**Note before laying:**

- Amount needed + 10% of the area
- Clean underlay, hard, flat, stable and strong
- Uneven surface = max 3 mm per 1,2 m
- Acclimatize the planks horizontally in the room for at least 48h!
- Important: room temperature = soil temperature = use temperature 18 ° C to 24 ° C

**Points to note about the configuration:**

- If underlay required: flameproof, vinyl approved (at least 400 kPa/m<sup>2</sup>, 1.5 mm, non-adhesive)
- On linoleum, wood-based flooring: 0,2 mm PE Films building for decoupling mandatory!
- The planks must be properly clicked in!
- Provide expansion joints to walls and fixed objects of 8-10 mm
- Maximum field size 10 x 10 m

Decor	Article No.	Description	EAN	Pack/Pallet
MY096-02	106202180	Basico, Ashton, 4,2 mm	7640165923061	48



The pictures may differ in color from the original product.

### Oak London

- ◇ Natural wood look
- ◇ Quiet and warm underfoot
- ◇ Only 4,2 mm mounting height
- ◇ Wear layer 0,3 mm
- ◇ **L 1220 x B 180 mm**
- ◇ Carton content = 10 planks = 2,196 m<sup>2</sup>
- ◇ 100% recyclable
- ◇ Simple, floating floor laying
- ◇ Patented Uniclic connection
- ◇ Low emissions (Certified A +)
- ◇ DIBT certified
- ◇ Sound reduction up to 5 dB
- ◇ Utilization class 23/31

**Note before laying:**

- Amount needed + 10% of the area
- Clean underlay, hard, flat, stable and strong
- Uneven surface = max 3 mm per 1,2 m
- Acclimatize the planks horizontally in the room for at least 48h!
- Important: room temperature = soil temperature = use temperature 18 ° C to 24 ° C

**Points to note about the configuration:**

- If underlay required: flameproof, vinyl approved (at least 400 kPa/m<sup>2</sup>, 1.5 mm, non-adhesive)
- On linoleum, wood-based flooring: 0,2 mm PE Films building for decoupling mandatory!
- The planks must be properly clicked in!
- Provide expansion joints to walls and fixed objects of 8-10 mm
- Maximum field size 10 x 10 m

Decor	Article No.	Description	EAN	Pack/Pallet
MB01117-08	106202181	Basico, Eiche London, 4,2 mm	7640165923078	48



The pictures may differ in color from the original product.

### Ibiza

- ◇ Natural wood look
- ◇ Quiet and warm underfoot
- ◇ Only 4,2 mm mounting height
- ◇ Wear layer 0,3 mm
- ◇ **L 609,6 x B 304,8 mm**
- ◇ Carton content = 12 planks = 2,23 m<sup>2</sup>
- ◇ 100% recyclable
- ◇ Simple, floating floor laying
- ◇ Patented Uniclic connection
- ◇ Low emissions (Certified A +)
- ◇ DIBT certified
- ◇ Sound reduction up to 5 dB
- ◇ Utilization class 23/31

**Note before laying:**

- Amount needed + 10% of the area
- Clean underlay, hard, flat, stable and strong
- Uneven surface = max 3 mm per 1,2 m
- Acclimatize the planks horizontally in the room for at least 48h!
- Important: room temperature = soil temperature = use temperature 18 ° C to 24 ° C

**Points to note about the configuration:**

- If underlay required: flameproof, vinyl approved (at least 400 kPa/m<sup>2</sup>, 1.5 mm, non-adhesive)
- On linoleum, wood-based flooring: 0,2 mm PE Films building for decoupling mandatory!
- The planks must be properly clicked in!
- Provide expansion joints to walls and fixed objects of 8-10 mm
- Maximum field size 10 x 10 m



Decor	Article No.	Description	EAN	Pack/Pallet
ORGM 2109-12	106202160	Basico, Ibiza, 4,2 mm	7640165923085	44



The pictures may differ in color from the original product.

## Palma

- ◇ Natural wood look
- ◇ Quiet and warm underfoot
- ◇ Only 4,2 mm mounting height
- ◇ Wear layer 0,3 mm
- ◇ **L 609,6 x B 304,8 mm**
- ◇ Carton content = 12 planks = 2,23 m<sup>2</sup>
- ◇ 100% recyclable
- ◇ Simple, floating floor laying
- ◇ Patented Uniclic connection
- ◇ Low emissions (Certified A +)
- ◇ DIBT certified
- ◇ Sound reduction up to 5 dB
- ◇ Utilization class 23/31

### Note before laying:

- Amount needed + 10% of the area
- Clean underlay, hard, flat, stable and strong
- Uneven surface = max 3 mm per 1,2 m
- Acclimatize the planks horizontally in the room for at least 48h!
- Important: room temperature = soil temperature = use temperature 18 ° C to 24 ° C

### Points to note about the configuration:

- If underlay required: flameproof, vinyl approved (at least 400 kPa/m<sup>2</sup>, 1.5 mm, non-adhesive)
- On linoleum, wood-based flooring: 0,2 mm PE Films building for decoupling mandatory!
- The planks must be properly clicked in!
- Provide expansion joints to walls and fixed objects of 8-10 mm
- Maximum field size 10 x 10 m



Decor	Article No.	Description	EAN	Pack/Pallet
MOA01204-03	106202161	Basico, Palma, 4,2 mm	7640165923092	44



The pictures may differ in color from the original product.

### Elba

- ◇ Natural wood look
- ◇ Quiet and warm underfoot
- ◇ Only 4,2 mm mounting height
- ◇ Wear layer 0,3 mm
- ◇ **L 609,6 x B 304,8 mm**
- ◇ Carton content = 12 planks = 2,23 m<sup>2</sup>
- ◇ 100% recyclable
- ◇ Simple, floating floor laying
- ◇ Patented Uniclic connection
- ◇ Low emissions (Certified A +)
- ◇ DIBT certified
- ◇ Sound reduction up to 5 dB
- ◇ Utilization class 23/31

#### Note before laying:

- Amount needed + 10% of the area
- Clean underlay, hard, flat, stable and strong
- Uneven surface = max 3 mm per 1,2 m
- Acclimatize the planks horizontally in the room for at least 48h!
- Important: room temperature = soil temperature = use temperature 18 ° C to 24 ° C

#### Points to note about the configuration:

- If underlay required: flameproof, vinyl approved (at least 400 kPa/m<sup>2</sup>, 1.5 mm, non-adhesive)
- On linoleum, wood-based flooring: 0,2 mm PE Films building for decoupling mandatory!
- The planks must be properly clicked in!
- Provide expansion joints to walls and fixed objects of 8-10 mm
- Maximum field size 10 x 10 m



Decor	Article No.	Description	EAN	Pack/Pallet
MOA01203-03	106202162	Basico, Elba, 4,2 mm	7640165923108	44



The pictures may differ in color from the original product.

## Manacor

- ◇ Natural wood look
- ◇ Quiet and warm underfoot
- ◇ Only 4,2 mm mounting height
- ◇ Wear layer 0,3 mm
- ◇ **L 609,6 x B 304,8 mm**
- ◇ Carton content = 12 planks = 2,23 m<sup>2</sup>
- ◇ 100% recyclable
- ◇ Simple, floating floor laying
- ◇ Patented Uniclic connection
- ◇ Low emissions (Certified A +)
- ◇ DIBT certified
- ◇ Sound reduction up to 5 dB
- ◇ Utilization class 23/31

### Note before laying:

- Amount needed + 10% of the area
- Clean underlay, hard, flat, stable and strong
- Uneven surface = max 3 mm per 1,2 m
- Acclimatize the planks horizontally in the room for at least 48h!
- Important: room temperature = soil temperature = use temperature 18 ° C to 24 ° C

### Points to note about the configuration:

- If underlay required: flameproof, vinyl approved (at least 400 kPa/m<sup>2</sup>, 1.5 mm, non-adhesive)
- On linoleum, wood-based flooring: 0,2 mm PE Films building for decoupling mandatory!
- The planks must be properly clicked in!
- Provide expansion joints to walls and fixed objects of 8-10 mm
- Maximum field size 10 x 10 m



Decor	Article No.	Description	EAN	Pack/Pallet
MO 2105-1	106202163	Basico, Manacor, 4,2 mm	7640165923115	44



The pictures may differ in color from the original product.

### Lowlands

- ◇ Natural wood look
- ◇ Quiet and warm underfoot
- ◇ Only 4,2 mm mounting height
- ◇ Wear layer **0,5 mm**
- ◇ **L 1220 x B 180 mm**
- ◇ Carton content = 10 planks = 2,196 m<sup>2</sup>
- ◇ 100% recyclable
- ◇ Simple, floating floor laying
- ◇ Patented Uniclic connection
- ◇ Low emissions (Certified A +)
- ◇ DIBT certified
- ◇ Sound reduction up to 5 dB
- ◇ Utilization class 33/42

#### Note before laying:

- Amount needed + 10% of the area
- Clean underlay, hard, flat, stable and strong
- Uneven surface = max 3 mm per 1,2 m
- Acclimatize the planks horizontally in the room for at least 48h!
- Important: room temperature = soil temperature = use temperature 18 ° C to 24 ° C

#### Points to note about the configuration:

- If underlay required: flameproof, vinyl approved (at least 400 kPa/m<sup>2</sup>, 1.5 mm, non-adhesive)
- On linoleum, wood-based flooring: 0,2 mm PE Films building for decoupling mandatory!
- The planks must be properly clicked in!
- Provide expansion joints to walls and fixed objects of 8-10 mm
- Maximum field size 10 x 10 m



Decor	Article No.	Description	EAN	Pack/Pallet
MO287L-05	106202200	Basico, Lowlands, 4,2 mm	7640165923344	48



The pictures may differ in color from the original product.

### Speyside

- ◇ Natural wood look
- ◇ Quiet and warm underfoot
- ◇ Only 4,2 mm mounting height
- ◇ Wear layer **0,5 mm**
- ◇ **L 1220 x B 180 mm**
- ◇ Carton content = 10 planks = 2,196 m<sup>2</sup>
- ◇ 100% recyclable
- ◇ Simple, floating floor laying
- ◇ Patented Uniclic connection
- ◇ Low emissions (Certified A +)
- ◇ DIBT certified
- ◇ Sound reduction up to 5 dB
- ◇ Utilization class 33/42

#### Note before laying:

- Amount needed + 10% of the area
- Clean underlay, hard, flat, stable and strong
- Uneven surface = max 3 mm per 1,2 m
- Acclimatize the planks horizontally in the room for at least 48h!
- Important: room temperature = soil temperature = use temperature 18 ° C to 24 ° C

#### Points to note about the configuration:

- If underlay required: flameproof, vinyl approved (at least 400 kPa/m<sup>2</sup>, 1.5 mm, non-adhesive)
- On linoleum, wood-based flooring: 0,2 mm PE Films building for decoupling mandatory!
- The planks must be properly clicked in!
- Provide expansion joints to walls and fixed objects of 8-10 mm
- Maximum field size 10 x 10 m

Decor	Article No.	Description	EAN	Pack/Pallet
MB1117-1	106202201	Basico, Speyside, 4,2 mm	7640165923351	48



The pictures may differ in color from the original product.

### Islands

- ◇ Natural wood look
- ◇ Quiet and warm underfoot
- ◇ Only 4,2 mm mounting height
- ◇ Wear layer **0,5 mm**
- ◇ **L 1220 x B 180 mm**
- ◇ Carton content = 10 planks = 2,196 m<sup>2</sup>
- ◇ 100% recyclable
- ◇ Simple, floating floor laying
- ◇ Patented Uniclic connection
- ◇ Low emissions (Certified A +)
- ◇ DIBT certified
- ◇ Sound reduction up to 5 dB
- ◇ Utilization class 33/42

**Note before laying:**

- Amount needed + 10% of the area
- Clean underlay, hard, flat, stable and strong
- Uneven surface = max 3 mm per 1,2 m
- Acclimatize the planks horizontally in the room for at least 48h!
- Important: room temperature = soil temperature = use temperature 18 ° C to 24 ° C

**Points to note about the configuration:**

- If underlay required: flameproof, vinyl approved (at least 400 kPa/m<sup>2</sup>, 1.5 mm, non-adhesive)
- On linoleum, wood-based flooring: 0,2 mm PE Films building for decoupling mandatory!
- The planks must be properly clicked in!
- Provide expansion joints to walls and fixed objects of 8-10 mm
- Maximum field size 10 x 10 m

Decor	Article No.	Description	EAN	Pack/Pallet
MO0404-6	106202202	Basico, Islands, 4,2 mm	7640165923368	48



The pictures may differ in color from the original product.

## Campbeltown

- ◇ Natural wood look
- ◇ Quiet and warm underfoot
- ◇ Only 4,2 mm mounting height
- ◇ Wear layer **0,5 mm**
- ◇ **L 1220 x B 180 mm**
- ◇ Carton content = 10 planks = 2,196 m<sup>2</sup>
- ◇ 100% recyclable
- ◇ Simple, floating floor laying
- ◇ Patented Uniclic connection
- ◇ Low emissions (Certified A +)
- ◇ DIBT certified
- ◇ Sound reduction up to 5 dB
- ◇ Utilization class 33/42

### Note before laying:

- Amount needed + 10% of the area
- Clean underlay, hard, flat, stable and strong
- Uneven surface = max 3 mm per 1,2 m
- Acclimatize the planks horizontally in the room for at least 48h!
- Important: room temperature = soil temperature = use temperature 18 ° C to 24 ° C

### Points to note about the configuration:

- If underlay required: flameproof, vinyl approved (at least 400 kPa/m<sup>2</sup>, 1.5 mm, non-adhesive)
- On linoleum, wood-based flooring: 0,2 mm PE Films building for decoupling mandatory!
- The planks must be properly clicked in!
- Provide expansion joints to walls and fixed objects of 8-10 mm
- Maximum field size 10 x 10 m

Decor	Article No.	Description	EAN	Pack/Pallet
MO287L-13B	106202203	Basico, Campbeltown, 4,2 mm	7640165923375	48



The pictures may differ in color from the original product.

### Inseln

- ◇ Natural wood look
- ◇ Quiet and warm underfoot
- ◇ Only 4,2 mm mounting height
- ◇ Wear layer **0,5 mm**
- ◇ **L 1220 x B 180 mm**
- ◇ Carton content = 10 planks = 2,196 m<sup>2</sup>
- ◇ 100% recyclable
- ◇ Simple, floating floor laying
- ◇ Patented Uniclic connection
- ◇ Low emissions (Certified A +)
- ◇ DIBT certified
- ◇ Sound reduction up to 5 dB
- ◇ Utilization class 33/42

#### Note before laying:

- Amount needed + 10% of the area
- Clean underlay, hard, flat, stable and strong
- Uneven surface = max 3 mm per 1,2 m
- Acclimatize the planks horizontally in the room for at least 48h!
- Important: room temperature = soil temperature = use temperature 18 ° C to 24 ° C

#### Points to note about the configuration:

- If underlay required: flameproof, vinyl approved (at least 400 kPa/m<sup>2</sup>, 1.5 mm, non-adhesive)
- On linoleum, wood-based flooring: 0,2 mm PE Films building for decoupling mandatory!
- The planks must be properly clicked in!
- Provide expansion joints to walls and fixed objects of 8-10 mm
- Maximum field size 10 x 10 m

Decor	Article No.	Description	EAN	Pack/Pallet
MJ6087-01	106202204	Basico, Inseln, 4,2 mm	7640165923382	48