



The pictures may differ in color from the original product.

Milano


- ◇ Natural stone look
- ◇ Quiet and warm underfoot
- ◇ Only 5 mm mounting height
- ◇ Wear layer 0,5 mm
- ◇ 605 x 304,8 mm (L x W)
- ◇ Carton content = 10 tiles = 1,84 m²
- ◇ 100% recyclable
- ◇ Phthalates free
- ◇ Patented Uniclic connection
- ◇ Low emissions (Certified A +)
- ◇ DIBT certified
- ◇ Sound reduction up to 6 dB
- ◇ Utilization class 33/42

Note before laying:

- Amount needed + 10% of the area
- Clean underlay, hard, flat, stable and strong
- Uneven surface = max 3 mm per 1,2 m
- Acclimatize the planks horizontally in the room for at least 48h!
- Important: room temperature = soil temperature = use temperature 18 ° C to 24 ° C

Points to note about the configuration:

- If underlay required: flameproof, vinyl approved (at least 400 kPa/m², 1.5 mm, non-adhesive)
- On linoleum, wood-based flooring: 0,2 mm PE Films building for decoupling mandatory!
- The planks must be properly clicked in!
- Provide expansion joints to walls and fixed objects of 8-10 mm
- Maximum field size 10 x 10 m



Decor	Article No.	Description	EAN	Pack/Pallet
215132	106202118	Starcllic Stone, Milano, 5 mm	0088969321510	32



The pictures may differ in color from the original product.

Bologna

- ◇ Natural stone look
- ◇ Quiet and warm underfoot
- ◇ Only 5 mm mounting height
- ◇ Wear layer 0,5 mm
- ◇ 605 x 304,8 mm (L x W)
- ◇ Carton content = 10 tiles = 1,84 m²
- ◇ 100% recyclable
- ◇ Phthalates free
- ◇ Patented Uniclic connection
- ◇ Low emissions (Certified A +)
- ◇ DIBT certified
- ◇ Sound reduction up to 6 dB
- ◇ Utilization class 33/42

Note before laying:

- Amount needed + 10% of the area
- Clean underlay, hard, flat, stable and strong
- Uneven surface = max 3 mm per 1,2 m
- Acclimatize the planks horizontally in the room for at least 48h!
- Important: room temperature = soil temperature = use temperature 18 ° C to 24 ° C

Points to note about the configuration:

- If underlay required: flameproof, vinyl approved (at least 400 kPa/m², 1.5 mm, non-adhesive)
- On linoleum, wood-based flooring: 0,2 mm PE Films building for decoupling mandatory!
- The planks must be properly clicked in!
- Provide expansion joints to walls and fixed objects of 8-10 mm
- Maximum field size 10 x 10 m



Decor	Article No.	Description	EAN	Pack/Pallet
215134	106202120	Starclik Stone, Bologna, 5 mm	0088969421517	32



The pictures may differ in color from the original product.

Assisi


- ◇ Natural stone look
- ◇ Quiet and warm underfoot
- ◇ Only 5 mm mounting height
- ◇ Wear layer 0,5 mm
- ◇ 605 x 304,8 mm (L x W)
- ◇ Carton content = 10 tiles = 1,84 m²
- ◇ 100% recyclable
- ◇ Phthalates free
- ◇ Patented Uniclic connection
- ◇ Low emissions (Certified A +)
- ◇ DIBT certified
- ◇ Sound reduction up to 6 dB
- ◇ Utilization class 33/42

Note before laying:

- Amount needed + 10% of the area
- Clean underlay, hard, flat, stable and strong
- Uneven surface = max 3 mm per 1,2 m
- Acclimatize the planks horizontally in the room for at least 48h!
- Important: room temperature = soil temperature = use temperature 18 ° C to 24 ° C

Points to note about the configuration:

- If underlay required: flameproof, vinyl approved (at least 400 kPa/m², 1.5 mm, non-adhesive)
- On linoleum, wood-based flooring: 0,2 mm PE Films building for decoupling mandatory!
- The planks must be properly clicked in!
- Provide expansion joints to walls and fixed objects of 8-10 mm
- Maximum field size 10 x 10 m



Decor	Article No.	Description	EAN	Pack/Pallet
215142	106202122	Starcllic Stone, Assisi, 5 mm	0088969221513	32