



UNDERLAY MAT LVT/SPC 1.5

Pressure, heat and sound insulation underlay mat made of organic latex foam.

- ◇ Format 1 x 10 m
- ◇ Strength 1,5 mm
- ◇ Enhanced walking comfort
- ◇ Sound and noise absorption (14-18 dB)
- ◇ Pressure-resistant (1677 kPa/m²) and highly elastic
- ◇ With integrated vapor barrier film
- ◇ Latex-based
- ◇ Renewable resource
- ◇ Recyclable raw material

Technical Specifications	Standard	LVT/SPC 1.5
Strength	EN 1849 - 1	1,5 mm
Specific weight	EN 1849 - 1	950 kg / m ³
Impact sound	UNE 104-B 717/12	14-18 dB
Walking sound	UNE 104-B 717/12	> 38,1 %
Fire behavior	DIN 4102	Cfl-S1
Thermal conductivity	EN 12667	0,0091 m ² K/w
Suitable for underfloor heating		Yes
Chair roll alignment		Yes

Processing notes

The underlay mat should be laid with white textile side up and the vapor barrier film down to the ground.

Article No.	Facido No.	Description	EAN	Pack/Pallet
125611	106102207	Underlay mat LVT/SPC 1.5, 1 x 10 m	8437005770416	40