



UNDERLAY MAT BIOlay 1.5

Pressure-stable, heat and sound insulation underlay made from organic latex and mineral fillers.

- ◊ Format 1 x 10 m
- ◊ Strength 1,5 mm
- ◊ Enhanced walking comfort
- ◊ Sound and noise absorption (20 dB)
- ◊ Pressure-resistant (1677 kPa/m²) and highly elastic
- ◊ With integrated vapor barrier film
- ◊ Made of BIO latex and mineral fillers
- ◊ Renewable resource
- ◊ Recyclable raw material

Technical Specifications	Standard	LVT/SPC 1.5
Strength	EN 1849 - 1	1,5 mm
Specific weight	EN 1849 - 1	950 kg / m ³
Impact sound	UNE 104-B 717/12	20 dB
Walking sound	UNE 104-B 717/12	38%
Fire behavior	DIN 4102	Bs:S1
Thermal conductivity	EN 12667	0,00912 m ² K/w
Compressive strength	DIN EN 826	≥ 666 kPa
Protection against moisture	DIN EN 12086	≥ 52 m
Suitable for underfloor heating		Yes
Chair roll alignment		Yes



Processing notes

The underlay matt should be laid with white textile side up and the vapor barrier film down to the ground.

Article No.	Facido No.	Description	EAN	Pack/Pallet
143642	106102208	Underlay mat BIOlay 1.5, 1 x 10 m	7640370940372	40