

IS = 14-18 dB

TRITTSCHALLDÄMMUNG (ΔL_w)

IMPACT SOUND REDUCTION / ISOLATION DU BRUIT
D'IMPACT / RIDUZIONE DEL RUMORE DA CALPESTIO




RWS = 38,1%

Ln, walk, A = 81,9 dB

GEHSCHALLVERBESSERUNG

REFLECTED WALKING SOUND / REDUCTION DU BRUIT DE
CHOC / RIDUZIONE DEL RIVERBERO DA CAMMINAMENTO



$\rho = 950 \text{ kg/m}^2$

DICHTE

DENSITY / DENSITE / DENSITA



e = 1,5 mm

DICKE


THICKNESS / ÉPAISSEUR / SPESSORE



R = 0,0091 m²K/W

WÄRMEWIDERSTAND

THERMAL RESISTANCE / RÉSISTANCE THERMIQUE /
RESISTENZA TERMICA



CS = >1677 kPa

DRUCKFESTIGKEIT

COMPRESSIVE STRENGTH / RÉSISTANCE À LA
COMPRESSION / RESISTENZA ALLA COMPRESSIONE



MONTAGEANLEITUNG

Installation Instructions / Instructions
d'installation / istruzioni di installazione

Bitte beachten Sie auch die Anweisungen des Bodenbelag-
Herstellers / Please also follow the flooring manufacturer's
instructions / S.v.p. suivez aussi les instructions du fabricant
du revêtement de sol / Seguir anachi le istruzioni del
produttore del pavimento

Hergestellt für:
HWZ International AG, Untere Gründlistrasse 23, 6055 Alpnach Dorf, Switzerland

